

Polaris

Tuft gauge	1/10 loop pile	ISO 2424
Pilecomposition	100% PA SDN	ISO 2424
Primary Backing	Woven	ISO 2424
Secondary backing	AB	ISO 2424
Width	400 cm ± 1%	EN 984
Pile Density	0,114 gr/cm ³	ISO 8543
Pile Weight	950 gr/m ²	ISO 8543
Total weight	AB : 1800 gr/m ² ± 15%	ISO 8543
Pile height	4 mm ± 2 mm	ISO 1766
Total Height	AB : 6 mm	ISO 1765
Number of knots	92.825 /m ² -7.5% .+10%	ISO 1763
Fire Classification	Cfl-S1	EN 13501-1
Transversal resistance	Ω	ISO 10965
Use Area	Heavy project use (33)	EN 1307
GUT Nr.	8E81C606	www.pro-dis.info
Thermal resistance	0,095 (0,95 TOG) M ² KW	ISO 8302
Light fastness	≥ 5	105-B02
Wearebility	≥ 4	105-X12
Water fastness	≥ 4	105-E01
Electrostatic charging	<2 kV	ISO 6356
Luxury class	LC2	EN 1307
Pictures	www.condorcontract.com	

Floorsymbols



Certificates

